PENTAIR JUNG PUMPEN

DRAINAGESET

DRAINAGE PUMPS

- Ready to connect
- Powerful drainage pump
- Large scope of supply
- For abrasive media
- Cooling jacket for motor housing
- SiC mechanical seal independent of rotation direction




DESCRIPTION

The Drainage Set reliably protects your building from mildly contaminated ground water. The set comes with the U6Drain ES drainage pump and is ready to plug in and use. The useful components contained in this set make it child's play to install and operate.

The powerful pump also handles drainge water with an abrasive sand content. Thanks to its slimline design, the drainage set fits in all standard drainage sumps with a sand trap from 280 mm internal diameter upwards. The mounting bracket stabilises the pump even in large sumps and ensures safe operation.

PERFORMANCE



Туре	Delivery head H[m]	1	2	3	4	5	6	7	8	9
Drainageset	Flow rate Q[m³/h]	15.5	14.0	12.5	11.0	9.0	7.5	5.5	3.5	1.5

We reserve the right to change specifications without notice. Pump performance is subject to ISO 9908 tolerances

to ISO 9906 tolerances

The minimum flow velocity in the pressure piping must be 0.7 m/s according to EN 12056. This data is represented in the performance curve as a limit of application.

D 129-2112

DRAINAGESET

DRAINAGE PUMPS

SCOPE OF SUPPLY

Drainage Set: Drainage pump U6 Drain ES, special float, swing-type check valve, hose nozzle with clamp, mounting bracket, 5 m lifting rope, 20 m cable, manual- 0- automatic

control switch.

Hose set: Elbow, 2×10^{-2} x hose nozzle, hose clamp, 15×10^{-2} m PVC spiral hose 0×10^{-2} 40 mm, hose clamp with wing bolt.

MECHANICAL DATA

Pump	Vertical single-stage	Shaft	Stainless steel
Free passage	10 mm	Impeller	Vortex impeller, GFK
Bearing	Ball bearings, grease-lubricat-	Motor housing	Stainless steel
	ed	Submersible	Yes
Seal on motor side	Rotary shaft seal	Mounted circuit	Yes
Oil chamber	Yes	Pressure outlet	1 1/4"
Seal on medium side	SiC mechanical seal	Weight	9 kg
Run dry protection	Yes		-


ELECTRICAL DATA

Voltage	1/N/PE~230 V	Type of enclosure	IP 68
Motor rating P1	0.75 kW	Insulation class	В
Motor rating P2	0.49 kW	Winding thermostat	Yes
Current	3.3 A	Motor protection	Integrated
Power line	20m S07RN-F	Plug	Safety
Wires	4G0,75		


DRAINAGESET

Type	Code No.	
Drainageset	JP43388	

Dimensions and switching points Drainage Set (mm)



Example of installation with hose set



DRAINAGESETDRAINAGEPUMPS

MECHANICAL ACCESSORY

		Code No.
1 Hose set	1 1/4" (DN32), 15 m PVC hose c/w elbow	JP43550

ELECTRICAL ACCESSORY

		Code No.
a Alarm unit		
AG20	Subm. ball contact switch, mains dependent, potential-free contact, 20 m cable	JP48851
(b) Rechargeable battery	for mains independent alarm	JP44850

DRAINAGESETDRAINAGEPUMPS